




VIERPUNTS FLENSLAGERBLOKKEN PTI

FOUR BOLT FLANGE UNITS PTI

Gegoten lagerblokken / FWS 25 U R3 - FWS 60 U R3

FWS U R3

Stelbout in binnenring
Driedubbele afdichting



Tripple-lip seal



Materiaal: gietijzeren behuizing, radiale insert kogellager, driedubbele afdichting

Type	Code	Afmetingen (mm)											Lagertype	Huis	(kg)	
		d	L	U	A	A ₁	A ₂	B	J	N	Q	V			Gewicht	Kap
FWS 25 U R3	310048205	25	95	38,8	29,0	11,0	19,0	34,1	70,0	11,5	1/8"	74	UC 205 R3	CJ05	0,77	KASK05
FWS 30 U R3	310048206	30	108	42,2	29,0	12,0	20,0	38,1	82,5	11,5	1/8"	85	UC 206 R3	CJ06	1,1	KASK06
FWS 35 U R3	310048207	35	118	46,4	30,5	12,5	21,0	42,9	92,0	14,0	1/8"	100	UC 207 R3	CJ07	1,44	KASK07
FWS 40 U R3	310048208	40	130	54,2	34,5	13,0	24,0	49,2	101,5	14,0	1/8"	110	UC 208 R3	CJ08	1,93	KASK08
FWS 45 U R3	310048209	45	137	54,2	35,0	13,0	24,0	49,2	105,0	14,0	1/8"	116	UC 209 R3	CJ09	2,15	Kap Ø45
FWS 50 U R3	310048210	50	143	60,6	39,0	13,0	28,0	51,6	111,0	18,0	1/8"	125	UC 210 R3	CJ10	2,33	KASK10
FWS 55 U R3	310048211	55	162	64,4	43,6	15,0	31,0	55,6	130,0	18,0	1/8"	140	UC 211 R3	CJ11	3,41	-
FWS 60 U R3	310048212	60	175	73,7	46,0	16,0	34,0	65,1	143,0	18,0	1/8"	150	UC 212 R3	CJ12	4,22	KASK12