

KETTINGWIELEN VOOR TAPERLOCKS MET GEHARDE TANDEN SPROCKETS FOR TAPER BUSHES WITH HARDENED TEETH



Simplex

3/8" x 7/32"

9,525 x 5,72 mm

Rol diam. 6,35 mm

06B-1



B1	C	r3
5,3	1	10

Materiaal: staal C45 - Tandens: HRc 50





Z	de	dp	code	dm	A	bus
17	55,5	51,83	B391330017	45	22	1008
19	61,6	57,86	B391330019	45	22	1008
21	67,6	63,90	B391330021	46	22	1008
23	73,7	69,95	B391330023	63	25	1210
25	79,7	75,99	B391330025	63	25	1210
27	85,7	82,04	B391330027	63	25	1210
30	94,8	91,12	B391330030	63	25	1210

1/2" x 5/16"

12,7 x 7,75 mm

Rol diam. 8,51 mm

08B-1



B1	C	r3
7,2	1,3	13

Materiaal: staal C45 - Tandens: HRc 50



Z	de	dp	code	dm	A	bus
15	66,5	61,80	B391340015	45	22	1008
17	74,5	69,11	B391340017	60	25	1210
19	82,5	77,15	B391340019	63	25	1210
21	90,6	85,21	B391340021	71	25	1610
23	98,7	93,26	B391340023	76	25	1610
25	106,7	101,32	B391340025	76	25	1610
27	114,8	109,39	B391340027	76	25	1610
30	126,9	121,49	B391340030	90	32	2012

KETTINGWIELEN VOOR TAPERLOCKS MET GEHARDE TANDEN SPROCKETS FOR TAPER BUSHES WITH HARDENED TEETH



Simplex

5/8" x 3/8"

15,875 x 9,65 mm

Rol diam. 10,16 mm

10B-1



B1	C	r3
9,1	1,6	16

Materiaal: staal C45 - Tandens: HRc 50





Z	de	dp	code	dm	A	bus
13	73,2	66,33	B391350013	47	22	1008
15	83,2	76,35	B391350015	60	25	1210
17	93,3	86,39	B391350017	71	25	1610
19	103,3	96,44	B391350019	75	25	1610
21	113,4	106,51	B391350021	76	25	1610
23	123,5	116,58	B391350023	76	25	1610
25	133,6	126,66	B391350025	90	32	2012
27	143,6	136,74	B391350027	90	32	2012
30	158,8	151,87	B391350030	90	32	2012

3/4" x 7/16"

19,50 x 11,68 mm

Rol diam. 12,07 mm

12B-1



B1	C	r3
11,1	2	19

Materiaal: staal C45 - Tandens: HRc 50



Z	de	dp	code	dm	A	bus
13	87,8	79,60	B391360013	60	25	1210
15	99,8	91,62	B391360015	70	25	1610
17	111,9	103,67	B391360017	76	25	1610
19	123,9	115,73	B391360019	90	32	2012
21	136,0	127,81	B391360021	102	44	2517
23	148,1	139,90	B391360023	108	44	2517
25	160,2	151,99	B391360025	108	44	2517
27	172,3	164,09	B391360027	108	44	2517
30	190,4	182,24	B391360030	108	44	2517

KETTINGWIELEN VOOR TAPERLOCKS MET GEHARDE TANDEN SPROCKETS FOR TAPER BUSHES WITH HARDENED TEETH



Simplex

1" x 17,02mm

25,4 x 17,02 mm

Rol diam. 15,88 mm

16B-1



B1	C	r3
16,2	2,5	26

Materiaal: staal C45 - Tandens: HRc 50





Z	de	dp	code	dm	A	bus
15	133,7	122,16	B391380015	76	38	1615
17	149,8	138,23	B391380017	90	32	2012
19	165,9	154,31	B391380019	108	44	2517
21	182,0	170,42	B391380021	110	44	2517
23	198,1	186,53	B391380023	110	44	2517
25	214,2	202,66	B391380025	110	44	2517
27	230,4	218,79	B391380027	110	44	2517
30	254,6	242,99	B391380030	120	44	2517

1"1/4 x 3/4"

31,75 x 19,56 mm

Rol diam. 19,05 mm

20B-1



B1	C	r3
18,5	3,5	32

Materiaal: staal C45 - Tandens: HRc 50



Z	de	dp	code	dm	A	bus
15	167,7	152,72	B391400015	110	44	2517
17	187,7	172,78	B391400017	110	44	2517
19	207,9	192,91	B391400019	110	44	2517
21	228,0	213,04	B391400021	120	44	2517
23	248,2	233,17	B391400023	120	44	2517
25	268,4	253,33	B391400025	120	44	2517